



Switch to SOLAR for
a Brighter Tomorrow

ORION SERIES

Mono-Perc Bifacial 132

475Wp-500Wp

Warranty



Product Warranty: 12 Years: Materials & Workmanship
Linear Performance Warranty: 27 Years
First Year Degradation: Up to 2.0%
Annual Degradation: 0.55% till 27 Years

KEY FEATURES



M10 cells for enhanced power generation.



Multi-busbar technology to minimize electrical losses.



Round ribbon connectors for improved light utilization.



Non-destructive cell cutting for improved reliability and lower chances of micro-cracks.



Half-cut cell technology for superior low-light performance.



Also available in Bifacial technology enabling power generation from both the sides.

CERTIFICATIONS



IS 14286:2010 | IEC 61215: 2005 IS | IEC 61730-2:2004 IS
| IEC 61730-1:2004 | IEC 62804 | IEC 61853 | IEC 61701



Performance under standard test conditions (1000w/m², AM 1.5, 25 °C)

ORION SERIES 120 Bi-Facial Gain @Different Albedo (%)																				
	Pm (Wp)	Voc (V)	Vm (V)	Isc (A)	Im (A)	Efficiency (%)		Pm (Wp)	Voc (V)	Vm (V)	Isc (A)	Im (A)	Efficiency (%)		Pm (Wp)	Voc (V)	Vm (V)	Isc (A)	Im (A)	Efficiency (%)
Front @STC	475	44.99	39.61	13.25	12.01	20.01		480	45.07	39.77	13.3	12.09	20.21		485	45.14	39.93	13.35	12.45	20.42
5%	499.50	44.99	39.61	13.91	12.61	21.04		504.86	45.07	39.77	13.97	12.69	21.26		510.25	45.14	39.93	13.82	14.02	21.49
10%	523.29	44.99	39.61	14.58	13.21	22.04		504.86	45.07	39.77	14.63	13.30	22.27		534.54	45.14	39.93	14.48	14.69	22.51
20%	570.86	44.99	39.61	15.90	14.41	24.04		576.98	45.07	39.77	15.96	14.51	24.30		583.14	45.14	39.93	15.79	16.02	24.56
Front @STC	490	45.21	40.06	13.39	12.24	20.64		495	45.34	40.24	13.45	12.32	20.85		500	45.40	40.32	13.49	12.42	21.06
5%	514.85	45.21	40.06	14.06	12.85	21.68		520.54	45.34	40.24	14.12	12.94	21.92		525.81	45.40	40.32	14.16	13.04	22.14
10%	539.37	45.21	40.06	14.73	13.46	22.71		545.33	45.34	40.24	14.80	13.55	22.97		550.85	45.40	40.32	14.84	13.66	23.20
20%	588.40	45.21	40.06	16.07	14.69	24.78		594.91	45.34	40.24	16.14	14.78	25.05		600.93	45.40	40.32	16.19	14.90	25.31

ELECTRICAL DATA PERFORMANCE

NOCT (Wp) at 45 ± 2 °C @800 W/m ²	IBMPH-475	IBMPH-480	IBMPH-485	IBMPH-490	IBMPH-495	IBMPH-500
Nominal Maximum Power (Pmax)	354.43	358.23	362.05	365.32	369.36	373.10
Optimum Operating Voltage (Vmp)	36.24	36.39	36.53	36.65	36.82	36.89
Optimum Operating Current (Imp)	9.78	9.85	9.91	9.97	10.03	10.11
Open Circuit Voltage (Voc)	41.85	41.93	41.99	42.06	42.18	42.23
Short Circuit Current (Isc)	10.83	10.87	10.92	10.95	11.00	11.03

Cell Temperature Coefficient

Short Circuit Current(α)	0.05 %/°C
Open Circuit Voltage(β)	-0.252 %/°C
Peak Power(δ)	-0.341 %/°C

Operating Conditions

Maximum System Voltage	DC1500V (IEC/UL)
Power Tolerance	0~+5W
Operating Temperature	-40°C~+85°C
Maximum Series Fuse Rating	30A
Mechanical Load Front Rear	5400Pa
Mechanical Load Back Rear	2400Pa
Bifaciality	75±5%

- Test uncertainty for Pmax ± 3%
- Bi-facial gain subject to mounting structure specifications and albedo % of ground


MODULE MECHANICAL DATA

SPECIFICATION DATA

Cell Type	Bifacial Mono-Perc , 132 Cells
Dimensions	2094x1134x35 mm
Weight	25 Kgs
Front Cover	3.2mm Low Iron and Tempered Glass with ARC Coating
Rear Cover	Transparent Backsheet
Frame Material	"Anodized Aluminium Alloy,
J-Box	IP68, Split JB
Cable	4mm ² (IEC) - 0.3 meter (Length)
Connectors	Mc4 Compatible Connector


- The specifications included in this datasheet are subject to change without notice.
- The electrical data given here is for reference purpose only.
- Please confirm your exact requirements with the sales representative while placing your order
- Refer installation Manual instructions & IB Solar warranty statement for terms & conditions

Engineering Design



Characteristics

Typical I-V Curves



4) Average relative efficiency reduction of 3% at 200 W/m² according to EN 60904-1.

Performance Warranty

